

Table of Contents

Smart Troffer Light	1
LED Troffer Light	2
LED Smart Vapor Tight Light	3
LED UFO Highbay Light 900A Series	4
LED UFO Highbay Light 800A Series	6
Linear High Bay 4th	7
Smart Canopy Light	9
LED GU24 Light	10
Smart FULL-Cut Wall Pack 10	12

PRICE SHEET

No.: MSQ-A211110
Date:2021.11.10

LED Smart Troffer Light Series

- AirTune LED Troffer delivers soft, glare-free, ambient lighting in a popular center-basket design.
- Working with Bluetooth APP to control the luminaires.
- Diffuser are extruded from impact modified polycarbonate, easy maintenance
- THD < 20%, PF: >0.9, CRI: >80
- Power efficiency up to 88%.
- Beam Angle: 120°
- Cold-rolled steel light body increases durability. Only 66mm (2.60") thickness.
- Lifespan: 50,000 hrs, Warranty: 5 Years



Product Code	Power Size	Dimension	Power	LEDs	CCT	Efficiency	Total Lumen	Unit Price US Stock
--------------	------------	-----------	-------	------	-----	------------	-------------	---------------------

Smart AirTune LED Troffer (T-Smart Light system) Single CCT

MA-HTR22CFLG-26W-40K-S	2x2' Troffer	603 *603 *66mm	26W	288 pcs	WW:3465±245K NW:3985±175K DW:5028±285K	145Lm/W	3770lm	US\$52.50
MA-HTR22CFLG-36W-40K-S	2x2' Troffer	603 *603 *66mm	36W	288 pcs	WW:3465±245K NW:3985±175K DW:5028±285K	125Lm/W	3750lm	US\$50.50
MA-HTR22CFLG-40W-40K-S	2x4' Troffer	603 *1213 *66mm	40W	384 pcs	WW:3465±245K NW:3985±175K DW:5028±285K	145Lm/W	5800lm	US\$73.50
MA-HTR22CFLG-50W-40K-S	2x4' Troffer	603 *1213 *66mm	50W	384 pcs	WW:3465±245K NW:3985±175K DW:5028±285K	125Lm/W	6250lm	US\$70.50

Product Code	Power Size	Dimension	Power	LEDs	CCT	Efficiency	Total Lumen	Unit Price US Stock
--------------	------------	-----------	-------	------	-----	------------	-------------	---------------------

Smart AirTune LED Troffer (T-Smart Light system) CCT Adjustable

MA-HTR14CFLG-36W-CCT-S	1x4' Troffer	1213 *303*66mm	36W	288 pcs X2	3000K-6500K	125Lm/W	4500lm	US \$62.50
MA-HTR22CFLG-36W-CCT-S	2x2' Troffer	603 *603 *66mm	36W	216 pcs X2	3000K-6500K	125Lm/W	4500lm	US \$80.50
MA-HTR24CFLG-50W-CCT-S	2x4' Troffer	603 *1213 *66mm	50W	288 pcs X2	3000K-6500K	125Lm/W	6250lm	US \$78.00

Note:

1. Expiration Date: within 30 days.
 2. Delivery Time: Generally 3-5 business days (weekend and holidays may take longer) .
 3. Payment: 100% T/T in advance.
 4. Bank's name: JP Morgan Chase Bank, N.A. (Swift Code#CHASUS33)
Bank Address: 1 Chase Manhattan Plaza,
New York, NY 10005, USA
Tel: 212-552-3819
- Routing No: 072000326
Account No: 931539675
Payable to: Morstar Inc.
Company Address: 12868 Farmington Road, Livonia, MI 48150
Tel: 734-469-4225

MORSTAR INC



12868 Farmington Road Livonia, Michigan 48150, USA Phone: +1-877-977-3732 FAX: +1-866-936-1782
 Email: catherine@morstar.com www.morstar.com

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED Troffer Light

- 120mm high, with blue tooth and smart control
- Input Voltage: 120-277V,
- 0-10V dimmable
- Jusinpower Driver, Sharkward sensor ANT-1C, flicker free
- Confirm to ETL cETL DLC FCC



Specification	Power	Unit Price US Stock	Logistic information			
MA-HTR22ARC-20W-T-CCT	20W	US\$90.45	L	W	H	
Size: 2*2			Carton Size(CM)			
Input Voltage: AC120-277V			QTY pieces per export carton:	2		
Luminous Flux: 2835LM			Cubic meter of export carton(M ³):	0.1350		
PF: >0.9 CRI: >90			Gross weight of export carton(kg):	11.5		
CCT & Efficacy : 2700-5700K, 2700K: 90lm/W, 5700K: 100lm/W			Net weight of export carton(kg):	10.9		
Lifespan: L70>50000hrs			QTY per 20" GP			
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" GP			
			QTY per 40" HQ			
MA-HTR22ARC-30W-T-CCT	30W	US\$92.50	L	W	H	
Size: 2*2			Carton Size(CM)			
Input Voltage: AC120-277V			QTY pieces per export carton:	2		
Luminous Flux: 2835LM			Cubic meter of export carton(M ³):	0.1350		
PF: >0.9 CRI: >90			Gross weight of export carton(kg):	17.5		
CCT & Efficacy : 2700-5700K, 2700K: 90lm/W, 5700K: 100lm/W			Net weight of export carton(kg):	16.5		
Lifespan: L70>50000hrs			QTY per 20" GP			
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" GP			
			QTY per 40" HQ			
MA-HTR24ARC-30W-T-CCT	30W	US\$129.00	L	W	H	
Size: 2*4			Carton Size(CM)			
Input Voltage: AC120-277V			QTY pieces per export carton:	2		
Luminous Flux: 2835LM			Cubic meter of export carton(M ³):	0.2560		
PF: >0.9 CRI: >90			Gross weight of export carton(kg):	17.5		
CCT & Efficacy : 2700-5700K, 2700K: 90lm/W, 5700K: 100lm/W			Net weight of export carton(kg):	16.5		
Lifespan: L70>50000hrs			QTY per 20" GP			
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" GP			
			QTY per 40" HQ			
MA-HTR24ARC-45W-T-CCT	45W	US\$134.00	L	W	H	
Size: 2*4			Carton Size(CM)			
Input Voltage: AC120-277V			QTY pieces per export carton:	2		
Luminous Flux: 2835LM			Cubic meter of export carton(M ³):	0.2560		
PF: >0.9 CRI: >90			Gross weight of export carton(kg):	13.0		
CCT & Efficacy : 2700-5700K, 2700K: 90lm/W, 5700K: 100lm/W			Net weight of export carton(kg):	12		
Lifespan: L70>50000hrs			QTY per 20" GP			
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" GP			
			QTY per 40" HQ			

PRICE SHEET

No.: MSQ-A211110
Date:2021.11.10

LED Smart Vapor Tight Light

- Premium High Power LED Chips and UL dual-channel Driver.
- Lumen efficacy up to 135lm/w.
- Weatherproof Polycarbonate Housing and Frosted Diffuser.
- Zone configurations and Scene management.
- Optimized design of double row, high quality of LEDs improves thermal resistance and heat dissipation.
- High end trimming.
- Apps available in IOS and Android Stores.
- ETL/DLC.pending



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MA-HVP451A-40W-L Input Voltage: AC120-277V (4 ft) Lumens Delivered: 5,400 lm Efficacy : 135 lm/W CRI : >80 CCT : 3000K / 4000K /5000K (Adjustable) Dimming: 0-10V Motion & daylight sensor options. Beam Angle: 120° PF: > 0.9 Surge protection: 4KV line-line, 6KV line-earth Lifespan: 50,000 hrs Warranty: 5 Years	40W	US\$65.00				
			Carton Size(CM)	120	11	10
			QTY pieces per export carton:	6		
			Cubic meter of export carton(M ³):	0.0132		
			Gross weight of export carton(kg):			
			Net weight of export carton(kg):			
			QTY per 20" GP	12726		
			QTY per 40" GP	26586		
			QTY per 40" HQ	30906		
MA-HVP851A-80W-L Input Voltage: AC120-277V (8 ft) Lumens Delivered: 10,800 lm Efficacy : 135 lm/W CRI : >80 CCT : 3000K / 4000K /5000K (Adjustable) Dimming: 0-10V Motion & daylight sensor options. Beam Angle: 120° PF: > 0.9 Surge protection: 4KV line-line, 6KV line-earth Lifespan: 50,000 hrs Warranty: 5 Years	80W	US\$115.00				
			Carton Size(CM)	240	11	10
			QTY pieces per export carton:	1		
			Cubic meter of export carton(M ³):	0.0264		
			Gross weight of export carton(kg):			
			Net weight of export carton(kg):			
			QTY per 20" GP	1060		
			QTY per 40" GP	2215		
			QTY per 40" HQ	2575		
MA-HVP451A-40W-H Input Voltage: AC120-347V (4 ft) Lumens Delivered: 5,400 lm Efficacy : 135 lm/W CRI : >80 CCT : 3000K / 4000K /5000K (Adjustable) Dimming: 0-10V Motion & daylight sensor options. Beam Angle: 120° PF: > 0.9 Surge protection: 4KV line-line, 6KV line-earth Lifespan: 50,000 hrs Warranty: 5 Years	40W	US\$69.00				
			Carton Size(CM)	120	11	10
			QTY pieces per export carton:	6		
			Cubic meter of export carton(M ³):	0.0132		
			Gross weight of export carton(kg):			
			Net weight of export carton(kg):			
			QTY per 20" GP	12726		
			QTY per 40" GP	26586		
			QTY per 40" HQ	30906		
MA-HVP851A-80W-H Input Voltage: AC120-347V (8 ft) Lumens Delivered: 10,800 lm Efficacy : 135 lm/W CRI : >80 CCT : 3000K / 4000K /5000K (Adjustable) Dimming: 0-10V Motion & daylight sensor options. Beam Angle: 120° PF: > 0.9 Surge protection: 4KV line-line, 6KV line-earth Lifespan: 50,000 hrs Warranty: 5 Years	80W	US\$117.50				
			Carton Size(CM)	240	11	10
			QTY pieces per export carton:	1		
			Cubic meter of export carton(M ³):	0.0264		
			Gross weight of export carton(kg):			
			Net weight of export carton(kg):			
			QTY per 20" GP	1060		
			QTY per 40" GP	2215		
			QTY per 40" HQ	2575		

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED UFO Highbay Light 900A Series

- Smooth and Stronger housing with good heat dissipation
- Input Voltage: 120V-277V
- THD < 20% , UGR < 28
- CCT: 2700K- 6000K
- Ceiling with loop, Ceiling with hook (Option)
- Finish: White / Black
- Certification: DLC, UL
- Widely used in the warehouses, gymnasiums and production assembly areas



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MA-HHB901A-100W-50K-85-S	100W	US\$90.00	Carton Size(CM)	28	28	18.5
Input Voltage: 120V-277V			QTY pieces per export carton:	1		
Efficiency: 150Lm/W			Cubic meter of export carton(M ³):	0.0145		
Total Lumen: 15,000Lm			Gross weight of export carton(kg):			
LEDs: 2835 320pcs			Net weight of export carton(kg):			
PF: >0.95 CRI: >70			QTY per 20" GP	1930		
Beam Angle: 85°			QTY per 40" GP	4033		
Regular Version, 1-10v Dimmable			QTY per 40" HQ	4688		
Lifespan: 50,000 hrs Warranty: 5 Years						
MA-HHB902A-150W-50K-85-S			150W	US\$98.00	Carton Size(CM)	32
Input Voltage: 120V-277V	QTY pieces per export carton:	1				
Efficiency: 150Lm/W	Cubic meter of export carton(M ³):	0.0195				
Total Lumen: 22,550Lm	Gross weight of export carton(kg):					
LEDs: 2835 456pcs	Net weight of export carton(kg):					
PF: >0.95 CRI: >70	QTY per 20" GP	1439				
Beam Angle: 85°	QTY per 40" GP	3006				
Regular Version, 0-10v Dimmable	QTY per 40" HQ	3495				
Lifespan: 50,000 hrs Warranty: 5 Years						
MA-HHB903A-200W-50K-85-S	200W	US\$121.00			Carton Size(CM)	36
Input Voltage: 120V-277V			QTY pieces per export carton:	1		
Efficiency: 150Lm/W			Cubic meter of export carton(M ³):	0.0272		
Total Lumen: 30,000Lm			Gross weight of export carton(kg):			
LEDs: 2835 624pcs			Net weight of export carton(kg):			
PF: >0.95 CRI: >70			QTY per 20" GP	1028		
Beam Angle: 85°			QTY per 40" GP	2149		
Regular Version, 1-10v Dimmable			QTY per 40" HQ	2498		
Lifespan: 50,000 hrs Warranty: 5 Years						
MA-HHB904A-240W-50K-85-S			240W	US\$123.50	Carton Size(CM)	36
Input Voltage: 120V-277V	QTY pieces per export carton:	1				
Efficiency: 150Lm/W	Cubic meter of export carton(M ³):	0.0272				
Total Lumen: 36,000Lm	Gross weight of export carton(kg):					
LEDs: 2835 780pcs	Net weight of export carton(kg):					
PF: >0.95 CRI: >70	QTY per 20" GP	1028				
Beam Angle: 85°	QTY per 40" GP	2149				
Regular Version, 1-10v Dimmable	QTY per 40" HQ	2498				
Lifespan: 50,000 hrs Warranty: 5 Years						

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED UFO Highbay Light 800 Series

- Fins design,advective holes and grooves in each fin, good for heat dissipation
- Input Voltage: AC100-277V
- Environment: Indoor / Wet, IP65
- CCT: 4000K-5000K-5700K-6500K
- Certification: DLC,UL
- Widely used in commercial application: Exhibition Room, Gas Station, Supermarket etc.



Specification	Power	Unit Price US Stock	Logistic information			
MA-HHB801A-100W-50K-110-S	100W	US\$78.00	L	W	H	
Input Voltage: AC100-277V			Carton Size(CM)	27	13	19.5
Efficiency: 140lm/W			QTY pieces per export carton:	1		
Total Lumen: 14,000lm/W			Cubic meter of export carton(M ³):	0.0068		
LEDs: LM80 2835			Gross weight of export carton(kg):			
PF: >0.9 CRI: >80			Net weight of export carton(kg):			
Beam Angle: 110°			QTY per 20" GP	4090		
Regular Version, 1-10v Dimmable			QTY per 40" GP	8547		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" HQ	9934		
MA-HHB802A-150W-50K-110-S			150W	US\$87.00	L	W
Input Voltage: AC100-277V	Carton Size(CM)	30			14	21
Efficiency: 140lm/W	QTY pieces per export carton:	1				
Total Lumen: 21,000lm/W	Cubic meter of export carton(M ³):	0.0088				
LEDs: LM80 2835	Gross weight of export carton(kg):					
PF: >0.9 CRI: >80	Net weight of export carton(kg):					
Beam Angle: 110°	QTY per 20" GP	3174				
Regular Version, 1-10v Dimmable	QTY per 40" GP	6632				
Lifespan: 50,000 hrs Warranty: 5 Years	QTY per 40" HQ	7709				
MA-HHB803A-200W-50K-110-S	200W	US\$100.00			L	W
Input Voltage: AC100-277V			Carton Size(CM)	34	14.7	21
Efficiency: 140lm/W			QTY pieces per export carton:	1		
Total Lumen: 28,000lm/W			Cubic meter of export carton(M ³):	0.0105		
LEDs: LM80 2835			Gross weight of export carton(kg):			
PF: >0.9 CRI: >80			Net weight of export carton(kg):			
Beam Angle: 110°			QTY per 20" GP	2667		
Regular Version, 1-10v Dimmable			QTY per 40" GP	5573		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" HQ	6478		
MA-HHB804A-240W-50K-110-S			240W	US\$105.00	L	W
Input Voltage: AC100-277V	Carton Size(CM)	34			14.7	21
Efficiency: 140lm/W	QTY pieces per export carton:	1				
Total Lumen: 33,600lm/W	Cubic meter of export carton(M ³):	0.0105				
LEDs: LM80 2835	Gross weight of export carton(kg):					
PF: >0.9 CRI: >80	Net weight of export carton(kg):					
Beam Angle: 110°	QTY per 20" GP	2667				
Regular Version, 1-10v Dimmable	QTY per 40" GP	5573				
Lifespan: 50,000 hrs Warranty: 5 Years	QTY per 40" HQ	6478				

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED UFO Highbay Light 800 Series

- Fins design,advective holes and grooves in each fin, good for heat dissipation
- Input Voltage: AC100-277V
- Environment: Indoor / Wet, IP65
- CCT: 4000K-5000K-5700K-6500K
- Certification: DLC,UL
- Widely used in commercial application: Exhibition Room, Gas Station, Supermarket etc.



Specification	Power	Unit Price US Stock	Logistic information		
---------------	-------	------------------------	----------------------	--	--

LED UFO Highbay Light Series (Beam Angle: 85° UGR<28)

MA-HHB801A-100W-50K-85-S	100W	US\$79.00			
Input Voltage: AC100-277V			L	W	H
Efficiency: 140lm/W			27	13	19.5
Total Lumen: 14,000lm/W			QTY pieces per export carton: 1		
LEDs: LM80 2835			Cubic meter of export carton(M ³): 0.0068		
PF: >0.9 CRI: >80			Gross weight of export carton(kg):		
Beam Angle: 85°			Net weight of export carton(kg):		
Regular Version, 1-10v Dimmable			QTY per 20" GP 4090		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" GP 8547		
			QTY per 40" HQ 9934		
MA-HHB802A-150W-50K-85-S	150W	US\$88.50			
Input Voltage: AC100-277V			L	W	H
Efficiency: 140lm/W			30	14	21
Total Lumen: 21,000lm/W			QTY pieces per export carton: 1		
LEDs: LM80 2835			Cubic meter of export carton(M ³): 0.0088		
PF: >0.9 CRI: >80			Gross weight of export carton(kg):		
Beam Angle: 85°			Net weight of export carton(kg):		
Regular Version, 1-10v Dimmable			QTY per 20" GP 3174		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" GP 6632		
			QTY per 40" HQ 7709		
MA-HHB803A-200W-50K-85-S	200W	US\$103.00			
Input Voltage: AC100-277V			L	W	H
Efficiency: 140lm/W			34	14.7	21
Total Lumen: 28,000lm/W			QTY pieces per export carton: 1		
LEDs: LM80 2835			Cubic meter of export carton(M ³): 0.0105		
PF: >0.9 CRI: >80			Gross weight of export carton(kg):		
Beam Angle: 85°			Net weight of export carton(kg):		
Regular Version, 1-10v Dimmable			QTY per 20" GP 2667		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" GP 5573		
			QTY per 40" HQ 6478		
MA-HHB804A-240W-50K-85-S	240W	US\$107.00			
Input Voltage: AC100-277V			L	W	H
Efficiency: 140lm/W			34	14.7	21
Total Lumen: 33,600lm/W			QTY pieces per export carton: 1		
LEDs: LM80 2835			Cubic meter of export carton(M ³): 0.0105		
PF: >0.9 CRI: >80			Gross weight of export carton(kg):		
Beam Angle: 85°			Net weight of export carton(kg):		
Regular Version, 1-10v Dimmable			QTY per 20" GP 2667		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" GP 5573		
			QTY per 40" HQ 6478		

PRICE SHEET

No.: MSQ-A211110
 Date:2021.10.21

LED Linear Low Bay Light Series (with Sensor)



- 2ft:110W MAX & 220W MAX available
- High luminous efficacy 135lm/w;
- High quality isolated driver; 1-10V dimming; Flicker free;
- PF 0.90, driver efficiency 87%; THD<20%;
- Installation: chain mounting;
- Suitable for dry/damp location;
- Designed for warehouses, gymnasiums, and industrial spaces;



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MA-HLHB-80W-50K-S						
Product Size: 2 ft Efficiency: 135Lm/W Total Lumen: 10,800lm LEDs: LM70 PF: >0.9 CRI: >80 CCT: 4000K & 5000K Regular Version, 1-10v Dimmable Lifespan: 50,000 hrs Warranty: 5 Years	80W	US\$101.00	Carton Size(CM)	61.5	25.3	21
			QTY pieces per export carton:	4		
			Cubic meter of export carton(M ³):	0.0327		
			Gross weight of export carton(kg):	31.4		
			Net weight of export carton(kg):	27.4		
			QTY per 20" GP	3424		
			QTY per 40" GP	7160		
			QTY per 40" HQ	8324		
			MA-HLHB1-110W-50K-S			
Product Size: 2 ft Efficiency: 135Lm/W Total Lumen: 14,850lm LEDs: LM70 PF: >0.9 CRI: >80 CCT: 4000K & 5000K Regular Version, 1-10v Dimmable Lifespan: 50,000 hrs Warranty: 5 Years	110W	US\$104.00	Carton Size(CM)	61.5	25.3	21
			QTY pieces per export carton:	4		
			Cubic meter of export carton(M ³):	0.0327		
			Gross weight of export carton(kg):	31.4		
			Net weight of export carton(kg):	27.4		
			QTY per 20" GP	3424		
			QTY per 40" GP	7160		
			QTY per 40" HQ	8324		
			MA-HLHB2-165W-50K-S			
Product Size: 2 ft Efficiency: 135Lm/W Total Lumen: 22,275lm LEDs: LM70 PF: >0.9 CRI: >80 CCT: 4000K & 5000K Regular Version, 1-10v Dimmable Lifespan: 50,000 hrs Warranty: 5 Years	165W	US\$127.00	Carton Size(CM)	61.5	33	21
			QTY pieces per export carton:	4		
			Cubic meter of export carton(M ³):	0.0426		
			Gross weight of export carton(kg):	40.6		
			Net weight of export carton(kg):	36.2		
			QTY per 20" GP	2624		
			QTY per 40" GP	5488		
			QTY per 40" HQ	6380		

PRICE SHEET

No.: MSQ-A211110
 Date:2021.10.21

LED Linear Low Bay Light Series (with Sensor)



- 2ft:110W MAX & 220W MAX available
- High luminous efficacy 135lm/w;
- High quality isolated driver; 1-10V dimming; Flicker free;
- PF 0.90, driver efficiency 87%; THD<20%;
- Installation: chain mounting;
- Suitable for dry/damp location;
- Designed for warehouses, gymnasiums, and industrial spaces;



Specification	Power	Unit Price US Stock	Logistic information			
MA-HLHB3-220W-50K-S	220W	US\$141.00		L	W	H
Product Size: 2 ft			Carton Size(CM)	61.5	45	21
Efficiency: 135Lm/W			QTY pieces per export carton:	4		
Total Lumen: 29,700lm			Cubic meter of export carton(M ³):	0.0581		
LEDs: LM70			Gross weight of export carton(kg):	47.7		
PF: >0.9 CRI: >80			Net weight of export carton(kg):	42.8		
CCT: 4000K & 5000K			QTY per 20" GP	1924		
Regular Version, 1-10v Dimmable			QTY per 40" GP	4024		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" HQ	4680		
MA-HLHB4-225W-50K-S			225W	US\$153.00		L
Product Size: 4 ft	Carton Size(CM)	118			33	21
Efficiency: 135Lm/W	QTY pieces per export carton:	2				
Total Lumen: 30,375lm	Cubic meter of export carton(M ³):	0.0816				
LEDs: LM70	Gross weight of export carton(kg):	31.1				
PF: >0.9 CRI: >80	Net weight of export carton(kg):	26.1				
CCT: 4000K & 5000K	QTY per 20" GP	686				
Regular Version, 1-10v Dimmable	QTY per 40" GP	1434				
Lifespan: 50,000 hrs Warranty: 5 Years	QTY per 40" HQ	1666				
MA-HLHB5-300W-50K-S	300W	US\$181.87				L
Product Size: 4 ft			Carton Size(CM)	118	33	21
Efficiency: 135Lm/W			QTY pieces per export carton:	2		
Total Lumen: 40,500lm			Cubic meter of export carton(M ³):	0.0816		
LEDs: LM70			Gross weight of export carton(kg):	33.3		
PF: >0.9 CRI: >80			Net weight of export carton(kg):	28.3		
CCT: 4000K & 5000K			QTY per 20" GP	686		
Regular Version, 1-10v Dimmable			QTY per 40" GP	1434		
Lifespan: 50,000 hrs Warranty: 5 Years			QTY per 40" HQ	1666		

MORSTAR INC

12868 Farmington Road Livonia, Michigan 48150, USA Phone: +1-877-977-3732 FAX: +1-866-936-1782
 Email: catherine@morstar.com www.morstar.com

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED Smart Canopy Light

- Input voltage: 120V-277V. AC120-347V, AC277-480V (Option)
- The canopy adopt to fins design, advective grooves between fins are good for heat dissipation.
- The light using professional light distribution technique, high light reflectivity reflectors 155 degree beam angle available; Light transmission rate of lens is over 90%.
- UL/cUL wet location listed.



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MA-EGC10A-28W-C-50K-S	28W	US\$98.00		L	W	H
Size: 10 Inch			Carton Size(CM)	60	33	33
Input Voltage: AC120-277V			QTY pieces per export carton:	4		
Lamp Bead Model: Sumsung			Cubic meter of export carton(M ³):	0.0632		
Efficacy : 120 lm/W Luminous Flux: 3360LM			Gross weight of export carton(kg):	11.0		
PF: >0.9 CRI: >80			Net weight of export carton(kg):	9.7		
Color Temperature: 4000K / 5000K / 5700K			QTY per 20" GP	1768		
Warranty: 5 Years Lifespan: 50,000 hrs			QTY per 40" GP	3700		
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" HQ	4300		
MA-EGC10A-40W-C-50K-S			40W	US\$100.00		L
Size: 10 Inch	Carton Size(CM)	60			33	33
Input Voltage: AC120-277V	QTY pieces per export carton:	4				
Lamp Bead Model: Sumsung	Cubic meter of export carton(M ³):	0.0632				
Efficacy : 120 lm/W Luminous Flux: 4800LM	Gross weight of export carton(kg):	11.0				
PF: >0.9 CRI: >80	Net weight of export carton(kg):	9.7				
Color Temperature: 4000K / 5000K / 5700K	QTY per 20" GP	1768				
Warranty: 5 Years Lifespan: 50,000 hrs	QTY per 40" GP	3700				
Certifications: UL&cUL, DLC V5.0 Premium	QTY per 40" HQ	4300				
MA-EGC10A-60W-C-50K-S	60W	US\$102.00				L
Size: 10 Inch			Carton Size(CM)	60	33	33
Input Voltage: AC120-277V			QTY pieces per export carton:	4		
Lamp Bead Model: Sumsung			Cubic meter of export carton(M ³):	0.0632		
Efficacy : 120 lm/W Luminous Flux: 7200LM			Gross weight of export carton(kg):	12.5		
PF: >0.9 CRI: >80			Net weight of export carton(kg):	11		
Color Temperature: 4000K / 5000K / 5700K			QTY per 20" GP	1768		
Warranty: 5 Years Lifespan: 50,000 hrs			QTY per 40" GP	3700		
Certifications: UL&cUL, DLC V5.0 Premium			QTY per 40" HQ	4300		
MA-EGC70A-60W-C-50K-S			70W	US\$104.50		L
Size: 10 Inch	Carton Size(CM)	60			33	33
Input Voltage: AC120-277V	QTY pieces per export carton:	4				
Lamp Bead Model: Sumsung	Cubic meter of export carton(M ³):	0.0632				
Efficacy : 120 lm/W Luminous Flux: 8400LM	Gross weight of export carton(kg):	12.5				
PF: >0.9 CRI: >80	Net weight of export carton(kg):	11				
Color Temperature: 4000K / 5000K / 5700K	QTY per 20" GP	1768				
Warranty: 5 Years Lifespan: 50,000 hrs	QTY per 40" GP	3700				
Certifications: UL&cUL, DLC V5.0 Premium	QTY per 40" HQ	4300				

MORSTAR INC

12868 Farmington Road Livonia, Michigan 48150, USA Phone: +1-877-977-3732 FAX: +1-866-936-178
 Email: catherine@morstar.com www.morstar.com

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED Bluetooth GU24 Light

- 9W GU24 Base LED Lamp (Normal/PIR/Bluetooth mode optional)
- Lampholder is an Impact-resistant construction design and integrated thermoforming process technology, beautiful and durable
- Matching PC frosted guard with high light transmittance, bright and soft light
- Keyless Lampholder – can be used with a standard wall switch
- Pull Chain Lampholder – ON/OFF with Pull Chain
- Lampholder with leads for easy installation.



Specification	Power	Unit Price US Stock	Logistic information			
MS707C-A	9W	US\$7.56	L	W	H	
Normal model: MS707C-UL; GU24 keyless lampholder; PC Cover and PBT Base; with GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL			Carton Size(CM)	40	16	35
			QTY pieces per export carton:	24		
			Cubic meter of export carton(M ³):	0.0224		
			Gross weight of export carton(kg):	5.0		
			Net weight of export carton(kg):			
			QTY per 20" GP	30000		
			QTY per 40" GP	62664		
			QTY per 40" HQ	72840		
MS707CW-A			9W	US\$9.72	L	W
Normal model: MS707C-UL; GU24 pull chain lampholder; PC Cover and PBT Base; with GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 CRI: >80 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL	Carton Size(CM)	42			30	44
	QTY pieces per export carton:	24				
	Cubic meter of export carton(M ³):	0.0554				
	Gross weight of export carton(kg):	8.0				
	Net weight of export carton(kg):					
	QTY per 20" GP	12120				
	QTY per 40" GP	25320				
	QTY per 40" HQ	29424				
MS707C-B	9W	US\$10.40			L	W
Bluetooth model: MS707C-UL; GU24 keyless lampholder; PC Cover and PBT Base; with Bluetooth GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 CRI: >80 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL			Carton Size(CM)	40	16	35
			QTY pieces per export carton:	24		
			Cubic meter of export carton(M ³):	0.0224		
			Gross weight of export carton(kg):	5.0		
			Net weight of export carton(kg):			
			QTY per 20" GP	30000		
			QTY per 40" GP	62664		
			QTY per 40" HQ	72840		
MS707CW-B			9W	US\$12.69	L	W
Bluetooth model: MS707C-UL; GU24 pull chain lampholder; PC Cover and PBT Base; with Bluetooth GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 CRI: >80 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL	Carton Size(CM)	42			30	44
	QTY pieces per export carton:	24				
	Cubic meter of export carton(M ³):	0.0554				
	Gross weight of export carton(kg):	8.0				
	Net weight of export carton(kg):					
	QTY per 20" GP	12120				
	QTY per 40" GP	25320				
	QTY per 40" HQ	29424				

MORSTAR INC



12868 Farmington Road Livonia, Michigan 48150, USA Phone: +1-877-977-3732 FAX: +1-866-936-1782
 Email: catherine@morstar.com www.morstar.com

PRICE SHEET

No.: MSQ-A211110
 Date:2021.11.10

LED Bluetooth GU24 Light

- 9W GU24 Base LED Lamp (Normal/PIR/Bluetooth mode optional)
- Lampholder is an Impact-resistant construction design and integrated thermoforming process technology, beautiful and durable
- Matching PC frosted guard with high light transmittance, bright and soft light
- keyless Lampholder – can be used with a standard wall switch
- Pull Chain Lampholder – ON/OFF with Pull Chain
- Lampholder with leads for easy installation.



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MS707C-P	9W	US\$9.59				
PIR motion sensor model: GU24 keyless lampholder; PC Cover and PBT Base; with PIR GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 CRI: >80 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL			Carton Size(CM)	40	16	35
			QTY pieces per export carton:	24		
			Cubic meter of export carton(M ³):	0.0224		
			Gross weight of export carton(kg):	5.0		
			Net weight of export carton(kg):			
			QTY per 20" GP	30000		
			QTY per 40" GP	62664		
			QTY per 40" HQ	72840		
MS707CW-P			9W	US\$11.68		
PIR motion sensor model: GU24 pull chain lampholder; PC Cover and PBT Base; with PIR GU24 LED Bulb, 9W Input Voltage: AC120V, 60HZ Efficacy : 88-100 lm/W Luminous Flux: 800LM PF: >0.9 CRI: >80 Color Temperature: 2700K/ 3000K / 4000K / 5000K Warranty: 3 Years Certifications: UL&cUL	Carton Size(CM)	42			30	44
	QTY pieces per export carton:	24				
	Cubic meter of export carton(M ³):	0.0554				
	Gross weight of export carton(kg):	8.0				
	Net weight of export carton(kg):					
	QTY per 20" GP	12120				
	QTY per 40" GP	25320				
QTY per 40" HQ	29424					

MORSTAR INC



12868 Farmington Road Livonia, Michigan 48150, USA Phone: +1-877-977-3732 FAX: +1-866-936-1782
 Email: catherine@morstar.com www.morstar.com

PRICE SHEET

No.: MSQ-A211110
 2021.11.10

LED Smart Full-Cut Wall Pack Light

- ◆ Junction Box installation available
- ◆ Photocell / Motion sensor optional
- ◆ Surge protection
- ◆ High brightness leds
- ◆ IP65 Waterproof
- ◆ Battery emergency optional
- ◆ 120-277V & 120-347VAC optional



Specification	Power	Unit Price US Stock	Logistic information			
			L	W	H	
MA-EWP905E-30W-3CCT-S	30W	US\$99.50				
Voltage: 120-277V CCT Selectable: 3000K/4000K/5000K Lumen Efficacy: 130LM/W±10% CRI: >70Ra, PF: 0.90 LED Qty:48 pcs Working Temp: -22°F to 113°F (-30°C to +45°C) Beam Angle: Type II/ Type III/ Type IV Housing: Die-cast Aluminum Warranty: 5 Years			Carton Size(CM)	26	20	26.5
			QTY pieces per export carton:	1		
			Cubic meter of export carton(M ³):	0.1378		
			Gross weight of export carton(kg):	2.0		
			Net weight of export carton(kg):	1.5		
			QTY per 20" GP	2000		
			QTY per 40" GP	3857		
			QTY per 40" HQ	4857		
MA-EWP906E-100W-3CCT-S	100W	US\$112.00				
Voltage: 120-277V CCT Selectable: 3000K/4000K/5000K Lumen Efficacy: 130LM/W±10% CRI: >70Ra, PF: 0.90 LED Qty:48 pcs Working Temp: -22°F to 113°F (-30°C to +45°C) Beam Angle: Type II/ Type III/ Type IV Housing: Die-cast Aluminum Warranty: 5 Years			Carton Size(CM)	29	24	19
			QTY pieces per export carton:	1		
			Cubic meter of export carton(M ³):	0.1339		
			Gross weight of export carton(kg):	3.0		
			Net weight of export carton(kg):	2.4		
			QTY per 20" GP	1556		
			QTY per 40" GP	3369		
			QTY per 40" HQ	3778		

Note:

1. Expiration Date: within 30 days.
2. Delivery Time: Generally 3-5 business days (weekend and holidays may take longer) .
3. Payment: 100% T/T in advance.
4. Bank's name: JP Morgan Chase Bank, N.A. (Swift Code#CHASUS33)
 Bank Address: 1 Chase Manhattan Plaza,
 New York, NY 10005, USA
 Tel: 212-552-3819
 Routing No: 072000326
 Account No: 931539675
 Payable to: Morstar Inc.
 Company Address: 12868 Farmington Road, Livonia, MI 48150
 Tel: 734-469-4225